

Page 1

DATE OF PREPARATION:

4-24-86

EMERGENCY PHONE NO: (818) 579-6270

SECTION I—PRODUCT IDENTIFICATION

PRODUCT FORMULA: 3-1H-3

PRODUCT NAME: URETHANE HARDENER

PRODUCT CHEMICAL FAMILY: ALIPHATIC POLYISOCYANATE

SECTION II—HAZARDOUS INGREDIENTS

[illegible]

SECTION III—PHYSICAL DATA

BOILING POINT: 258.8°F

SPECIFIC GRAVITY: 1.06

VAPOR DENSITY (AIR = 1): HEAVIER

% VOLATILE BY VOLUME: 30%

SOLUBILITY IN WATER: NEGLIGIBLE

EVAPORATION RATE: FASTER

VAPOR PRESSURE: @20°C 8.0 mm.Hg

(BUTYL ACETATE = 1)

SECTION IV—FIRE AND EXPLOSIVE HAZARD DATA

FLASH POINT: 91 °F. TCC LEL: 1.0 % by Volume UEL: 7.6 % By Volume

EXTINGUISHING MEDIA: Foam, Dry Chemical, CO² and/or Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS:

During a fire, irritating and toxic gases and smoke are present from decomposition. Isolate from heat, sparks and open flames. Closed containers may burst when exposed to extreme heat. Vapors form an explosive mixture in air between the upper and lower explosive limits.

EVACUATION PROCEDURES: Full emergency equipment with self-contained breathing apparatus should be worn by firefighters.